

SAMPO

42" Plasma HDTV/Multimedia Display Monitor

PME-42S6



- High Contrast Ratio (600:1)
- 1080i, 720p, 480p, 480i Digital Signal Compatibility
- Multi-Video System Supported: NTSC/PAL, HDTV
- Multi-Scanning PC Monitor Support Up to 1024x768
- Multiple Inputs with 2 Sets Progressive Component Video Connections
- PIP/POP
- Attachable NTSC Tuner Card
- Digital Visual Interface (DVI)

PME-42S6 Pre- Specifications

DISPLAY	Screen Size (W x H)	920 mm x 518 mm (42" Diagonal)
	Aspect Ratio	16:9
	Number of Pixels	852 (H) x 480 (V)
	Dot Pitch	1.08 mm
	Contrast Ratio (Normal Mode/High Brightness Mode)	600:1
	Brightness (Normal Mode/High Brightness Mode)	500 cd/m ²
	Displayable Colors	16.77 Million Colors
	Viewing Angle	160
SIGNALS	Synchronization Range	
	Horizontal Frequency	15 kHz ~ 91 kHz
	Vertical Frequency	50 Hz ~ 85 Hz
	Video System	480i, 480p, 720p, 1080i SDTV/EDTV/HDTV*, NTSC/PAL
	RGB Resolution	Up to 1280 x 1024 (XGA)
INPUT/OUTPUT	DVI Input	DVI 24-pin x1
	RGB Input	D-Sub 15-pin x 1
	RGB Output	D-Sub 15-pin x 1
	Audio Input	5W x2
Video Capability (Optional)	NTSC Tuner	181CH
	Composite	RCA-pin x1
	S-Video Input	Mini DIN 4-pin x 1
	Audio Input	RCA-pin Type (L/R) x 6
	Audio Output	RCA-pin Type (L/R) x 1
	Component Video Signal	RCA-pin x 2 (Y/CB.CR, Y/PB/PR Auto Detect)
CONTROL PORT	RS-232C	D-Sub 9-pin x 1
	USB	USB B Type x 1
GENERAL	Power Supply	AC 100~240 V, 50/60 Hz
	Power Consumption	350 W
	Dimensions (W x H x D)	(Without Stand) 40.9" x 25.5" x 3.7"/ 1040 mm x 648 mm x 95 mm (With Stand) 40.9" x 27.2" x 14.7"/1040 mm x 690 mm x 375 mm



SAMPO
Sampo Technology B.V.

FORTUNAWEG 4, 3113AN
SCHIEDAM, THE NETHERLANDS
TEL:31-10-473-0844 FAX:31-10-473-1314
e-mail: joseph.shih@sampotech.nl
<http://www.sampotech.com> (Europe Area)